

H₂

CO

CH₄

O₂

Neon

CO₂


N₂

chromaTCD

Universal Detector

Continuous permanent gases monitoring


Automated system for measurements in the range: ppm or %



Model: C41022

Applications of the chromaTCD:

- Pure gas quality control : UHP (Ultra High Purity)
- Laboratory process
- Fermentation control
- O₂ / CO₂ / CO control
- Measurement of Neon / Hydrogen
- CO / CO₂ / CH₄ / HCHO with methanizer and FID in option



Chromatotec® is specialised in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt).
Please visit our website for more details.

Updated: April 2014

chromaTCD

Universal Detector

Continuous permanent gases monitoring

Automated system for measurements in the range: ppm or %



Principle:

The chromaTCD is an automatic, industrial or laboratory gas analyzer. The temperature setting is isothermal. The sample comes through the sampling **loop**. Then the sample is injected into an analytical column (with an automatic valve) for separation. Different column can be used (e.g. packed column). After separation, the amount of each compound is measured using an universal detector, the catharometer. An oven is installed in order to allow the **regeneration** (to avoid contamination) of the column **at 250°C**.

A pressure safety is inserted just after the detector in order to protect its wires.

The catharometer detector:

The Thermal Conductivity Detector (TCD) can detect all kind of compounds. The Wheatstone bridge is made of 4 Tungsten-Rhenium wires. It works with **constant current** or **constant voltage**. With the detector, a thermal conductivity difference between the reference cell (carrier gas) and the measure cell (outlet of the column) is measured. This value is transferred to an electrometer and the generated signal is proportional to the compounds concentration in the sample. The signal is then transferred to the CPU board and the microprocessor processes the data (integration, mass or concentration calcul, peaks identification...).

The different **parameters** (data, chromatogram, integration report...) are **transferred via a RS-232** port and they are visualised and reprocessed with our VISTACHROM software.

VISTACHROM® software:

The software developed by Chromatotec® allows:

- **Remote control**
- Full traceability with on board archiving of results
- **Program to stop the detector filament** (to protect them) inside a sequence (e.g. column cleaning)
- Programation and control of threshold alarms
- **Ponctual (laboratory) or continuous measurement**
- Data export by MODBUS / JBUS / MGS1 / 4-20mA / 0-10V

Options:

- Gas cleaner
- Modul 4 x analog output 4-20 mA or 0-10 V
- Alarms module
- **Automatic results validation**
- 24 V power supply
- **Explosion proof Exp box – Ex Specification Class1 Div2, groupC&D**
- Hydrogen and Nitrogen generator
- Multiple stream selector (2 to 10 streams with one analyzer)
- Carrier gas purificator
- **Sampling pump in 24V DC or airmoPUMP (XXX901 or XXX915)**
- Pressure and temperature measure
- **Mass Flow Controller** (MFC, in order to improve dilution precision and so calibration quality)

Product technical specifications:

Permanent and/or organic gas analysis:

- Neon, H₂, O₂, N₂, CH₄, CO, CO₂, CHX...

Detection limit:

- Neon and H₂ ≤ 2 ppm

Detection range:

- ppm to %. Depending on the options (loop and amplification)

Relative Standard Deviation: Repeatability

- RSD < 5% over 48h (concentration)
- RSD < 0.6% over 48h (retention time)

Results:

- Full result storage (data and graphics)
- Output 4 x 4-20 mA (in option)
- Communication protocol MODBUS (in option)
- Alarm module

Cycle time:

- 10 minutes for H₂ and for O₂ / N₂

Gas supply:

- He as carrier gas (inlet: 3.5 bar ; 1/16" swagelock)
- Calibration inlet : 1 bar ; 1/16" swagelock
- Sample inlet : 1 bar ; 1/16" swagelock

Volume sampled:

- 0.1 to 2 mL depending on application and detection range

Power supply:

- Main (230V / 115V 50 Hz/60Hz)
- Battery 24V (option)

Electric consumption:

- Average : 100 VA; Peak : 200 VA

Dimensions and weight:

- Rack: 19" (4U)
- Height: 177 mm
- Width: 482 mm
- Depth: 660 mm
- Net weight of analyser: 20 kg

If option C41022, rack 5U

To order:

chromaTCD (integrated computer 5U)
airmoPUMP
airmoPUMP for 6 ways (need a multiplexor)
ChromaCO (CO, CH₄, CO₂) for LDL in ppb

Model:

C41022
XXX901
XXX915
C11000

Chromatotec® is continuously improving its products, therefore these specifications are subject to change without notice

To contact us: info@chromatotec.com



NORTH AMERICA

CHROMATOTEC Inc.
18333 Egret Bay Blvd, Suite 270,
Houston TX 77058 - USA
Phone: +1 (281) 335 4944
Fax: +1 (281) 335 4943

EUROPE

AIRMOTEC AG SAS
15 rue d'Artiguelongue
33240 Saint-Antoine - FRANCE
Phone: +33 (0) 557 940 626
Fax: +33 (0) 557 940 620

ASIA

CHROMATOTEC Trading (Beijing) Co., Ltd.
Room 1806, Building 1,
Wanda Plaza, No.93, Jianguo Avenue,
Chaoyang District,
Beijing 100022 - CHINA
Phone : +86 (0) 105 960 3283